




Solaris Volume Manager: Debugging Tips





Solaris Volume Manager Debugging Tips

- Environment variables
- Dtrace
- MDB dcmds
- Compilation options

`



Environment Variables

- MD_DEBUG switch
 - > Set as env variable, comma separated list of options
 - > Acts in different ways to different code modules
 - Usually good for on-site info gathering and lab tests
- META_SP_DEBUG
 - > Set as env variable, no value required
 - > Enables additional messaging in soft partition code

Copyright 2006 Sun Microsystems, Inc. All rights reserved.



MD_DEBUG Options

- Metastat options :
 - > SETINFO print detailed metaset information
 - > STAT print detailed status information
- Libmeta code options :
 - > DEVADM enables messages in meta_devadm code
 - > FAILFAST={NONE,DRIVER,DEBUG,HALT,PANIC} controls failfast mode for taking MH diskset drives
 - NOTHREAD Forces MH set cmd to run as a single thread

,



MD_DEBUG Options

- Libmeta code options :
 - > DEVID Warn if a device has no devid
 - > RENAME / EXCHANGE Enable verbose messages in metarename code
 - > NODAEMON Forces resyncs to run in the foreground
 - MALLOC prints malloc() debug info in md_init_nosig and md_exit
 - > RPC Enables messages in meta_client_create_retry()

,



Dtrace

- Useful tool for root causing functional and performance issues in user, daemon, and kernel code
- Scripts are easy enough to generate and fine tune that they are not usually kept around.



MDB dcmds

- Integrated in S10 and above
- Provide means to
 - > Dump SVM structures
 - > Walk SVM namespace entries
 - > Dump hotspare pools

`



MDB dcmds - S10

dumphotspare
dumpnamespace
dumpsetaddr
md_verbose
dcmds
metaset
metastat

simple_de_ic

- dump the hot spare pools
 - dump the SVM name space
- dump the SVM set addresses
- toggle verbose mode for SVM
- list SVM metasets
- list SVM metadevices
 - simple mddb_de_ic_t

•



Conditional Compilation Support

- Debug compile time options
 - rpc.mdcommd
 - DEBUG in both libmeta and rpc.mdcommd turns on debug output for the change log
 - rpc.metad
 - DEBUG will turn on debug functions but there are currently no calls to these functions
 - rpc.metamedd
 - DEBUG will turn on debug functions but there are currently no calls to these functions
 - rpc.metamhd
 - DEBUG will turn on debug functions but there are currently no calls to these functions



SVM Debugging Tips